

## TECHNICAL SPECIFICATION

Applications                      Trailer / Tanker / Spreader  
 Description                      FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle.

**Pattern Name**                **FL 639**  
 Version                          STANDARD  
 Type                              TL  
 Tire Size                        560/45 R 22.5  
 LI/SS                            152 D/163 A8



Dimensions (U/M International standard)  
 Section Width (mm)            543  
 Overall Diameter (mm)        1076  
 Static Loaded Radius (mm)    484  
 Rolling Circumference (mm) 3303  
 SRI                                525  
 Rim Rec                         AG 16.00

### LOAD CAPACITY TABLE (kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1040	1200	1360	1620	1910	2170	2430	2720	2980	3235
65	1140	1320	1495	1790	2095	2380	2700	2960	3270	3550
50	1380	1595	1810	2150	2540	2900	3240	3615	3960	4300
40	1560	1805	2050	2450	2880	3270	3675	4090	4485	4875
25	1800	2080	2360	2820	3310	3775	4230	4700	5165	5610
10	2045	2365	2685	3200	3775	4300	4820	5350	5880	6390